

Declaration of Conformity

R&TTE Directive:	2006/95/EC Low Voltage Directive 2004/108/EC Electrical Equipment EMC Compatibility
Issued:	27 August 2009
Manufacturer:	Davis Instruments Corp., 3465 Diablo Avenue, Hayward, CA 94545, USA
Responsible Person:	Mr. James S. Acquistapace, Chairman Davis Instruments Corp., 3465 Diablo Avenue, Hayward, CA 94545, USA
Model Numbers:	6152CEU, 6152UK, 6162CEU, 6162CUK, 6316CEU, 6316CUK 6322C, 6327C, 6311VP2, 6410, 6420, 6440, 6450, 6470, 6490, 6673 6510SER, 6510USB, 6555, 6540, 6544, 6550, 6560, 6533 7400EU, 7400UK, 7425EU, 7425UK, 7425CSEU, 7425CSUK 7817, 7852, 7852M, 7911, 7862, 7855, 7870, 7720, 7747 6610, 7707
Product Description:	The Vantage Pro2 and Vantage Vue product line is a set of weather monitoring devices that transmit and receive weather data. These are accessories (spare parts) for the Vantage Pro2 and Vantage Vue product line. Products including rain collector, anemometer, humidity sensor, temperature sensor, leaf wetness sensor, solar sensor, UV sensor, and soil moisture sensor. Also includes software and installation parts.
Declared Frequency:	None

I, the undersigned, declare that the equipment specified above complies with the essential protection requirements of the R&TTE Directive 1995/5/EC.

Signature


James S. Acquistapace, Chairman

Date: December 4, 2009

WEATHER STATION SENSOR ACCURACY, RESOLUTION AND RANGE

Function		Vantage Pro2	Vantage Vue	Perception II	Weather Wizard III	U.S.A. Units			Metric Units			Except for rainfall, all variables are measured in U.S. units of measure and rounded to the nearest metric unit shown in the "Resolution" column.
						RESOLUTION	RANGE	ACCURACY ±	RESOLUTION	RANGE	ACCURACY ±	
AGRICULTURAL	Evapotranspiration	●				0.01"	0 to 199.99"	5%	0.1 mm	0 to 1999.9 mm	5%	
	Growing Degree-Days	○				0.1 Degree-Day	Unlimited		0.1 Degree-Day	Unlimited		
	Cooling/Heating Degree-Days	○	✓			0.1 Degree-Day	Unlimited		0.1 Degree-Day	Unlimited		
	Leaf Wetness	●				1	0 to 15	0.5	1	0 to 15	0.5	
	Soil Moisture	●				1 cb	0 to 200 cb		1 cb	0 to 200 cb		
BAROMETRIC PRESSURE	Barometric Pressure (Elevation range: -999' to +15,000'; -600 to +4570 m)	✓	✓			0.01" Hg	16" to 32.5" Hg	0.03" Hg	0.1 mm Hg 0.1 mb	410 to 820 mm Hg 540 to 1100 mb or hPa	0.8 mm Hg 1.0 mb or hPa	
	Barometric Pressure (Elevation range: -1990' to +12,500'; -600 to +3810 m)			✓			18" to 32.5" Hg	0.05" Hg	0.1 mm Hg 0.1 mb	460 to 820 mm Hg 610 to 1100 mb or hPa	1.3 mm Hg 1.7 mb	
	Three-Hour Trend	✓	✓			Slow ≥ 0.02" Hg Rapid ≥ 0.06" Hg	5-Position Arrow		Slow ≥ 0.5 mm (0.7 mb) Rapid ≥ 1.5 mm (2 mb)	5-Position Arrow		
	One-Hour Trend			✓		Change ≥ 0.02" Hg	3-Position Arrow		Change ≥ 0.5 mm (0.7 mb)	3-Position Arrow		
HUMIDITY	Inside Humidity	✓	✓			1%	0% to 100%	3%	1%	0% to 100%	3%	
				✓			10% to 90%	5%		10% to 90%	5%	
	Outside Humidity	✓	✓			1%	0% to 100%	3%	1%	0% to 100%	3%	
	Inside Dew Point	○	○			0.1°F	-60° to +140°F	3°F	0.1°C	-50° to +60°C	1.5°C	
Outside Dew Point			○			-60° to +140°F	5°F	2.5°C				
		✓	✓			1°F	-105° to +130°F	3°F	1°C	-76° to +54°C	1.5°C	
RAINFALL	Rainfall	✓	✓			0.01"	0 to 199.99"	4%	0.2 mm	0 to 6553 mm	4%	
				●	0 to 99.99"		Day: 0 to 999.8 mm Total: 0 to 9999 mm					
	Rate of Rainfall	✓				0.01"	0 to 96"/hr	5% ≤ 5"/hr	0.1 mm	0 to 2438 mm/hr	5% ≤ 127 mm/hr	
		✓			0 to 40"/hr		0 to 1016 mm/hr					
SOLAR & UV	Solar Radiation	●				1 W/m2	0 to 1800 W/m2	5%	1 W/m2	0 to 1800 W/m2	5%	
	Solar Energy	○				0.1 Ly	1999.9 Ly	5%	0.1 Ly	1999.9 Ly	5%	
	UV Dose	●				0.1 MEDs	0 to 199 MEDs	5%	0.1 MEDs	0 to 199 MEDs	5%	
	UV Index	●				0.1	0 to 16	5%	0.1	0 to 16	5%	
TEMPERATURE	Inside Temperature	✓	✓	✓	✓	0.1°F	+32° to +140°F	1°F	0.1°C	0° to +60°C	0.5°C	
	Outside Temperature (ISS)	✓	✓		✓	0.1°F	-40° to +150°F	1°F	0.1°C	-40° to +65°C	0.5°C	
	Outside Temp (Temp Stn)	●				1°F	-40° to +150°F	1°F	1°C	-40° to +65°C	0.5°C	
	Soil or Water Temperature	●				1°F	-40° to +150°F	1°F	1°C	-40° to +65°C	0.5°C	
	Inside Heat Index	○	○			0.1°F	+30°F to +165°F	3°F	0.1°C	-1°C to +74°C	1.5°C	
				○				5°F			2.5°C	
	Outside Heat Index	✓	✓			1°F	-40° to +165°F	3°F	1°C	-40° to +74°C	1.5°C	
	Temp-Hum-Sun-Wind Index	●				1°F	-90° to +165°F	4°F	1°C	-68° to +74°C	2°C	
Wind Chill	✓	✓		✓	1°F	-110° to +135°F	2°F	1°C	-79° to +57°C	1°C		
TIME/DATE	Time	✓	✓			1 minute	12/24 hours	8 sec/mo 15 sec/mo	1 minute	12/24 hours	8 sec/mo 15 sec/mo	
				✓	✓							
	Date	✓	✓			month/day	Leap Year	8 sec/mo	day/month	Leap Year	8 sec/mo	
			✓	✓			365 days	15 sec/mo			365 days	15 sec/mo
	Sunrise & Sunset	✓	✓	○	○	1 minute	12 hours	1 minute	1 minute	24 hours	1 minute	
WIND	Wind Direction	✓	✓			1°	0° to 360°	3°	1°	0° to 360°	3°	
				✓		1° or 10°		7°			1° or 10°	7°
	Compass Rose	✓	✓		✓	22.5°	16 compass points		22.5°	16 compass points		
	Wind Speed	✓	✓		✓	1 mph 1 knot	2 to 150 mph 2 to 130 knots	5%	0.1 m/s 1 km/hr	1 to 67 m/s 3 to 241 km/hr	5%	
	Direction of High Speed	✓	✓			22.5°	16 compass points		22.5°	16 compass points		
	Wind Run	○	○		○	0.01 mph 0.01 knot	Unlimited	5%	0.01 m/s 0.01 km/hr	Unlimited	5%	

- ✓ Included
 - Optional sensor required, shown on console
 - Optional, requires WeatherLink.
- Growing degree-days also requires Ag/Turf Management Module. Solar Energy requires Solar Radiation sensor.

"Resolution" refers to the number of digits or decimal places displayed on the console. For metric units, this is not the actual unit of measure except for rainfall. Our rain collector measures in true 0.01" or 0.2 mm increments. All other weather variables are measured and accumulated in U.S. units of measure, which are then converted to metric units for display purposes.

For complete specifications, visit our website at www.davisnet.com, then click on Support » Weather Support » Specification Sheets.

Weather Wizard III calculates and displays wind chill according to the original National Weather Service Formula. A new formula was adopted in 2001. For wind chill using this formula, view the data using WeatherLink or choose Vantage Pro2 or Vantage Vue instead.